



# Globestock Engineering Ltd.

Manufacturers of Safety & Fall Arrest Equipment

Mile Oak Industrial Estate, Maesbury Road, Oswestry, Shropshire SY10 8GA

Tel: 01691 654966

Fax: 01691 661726

e-mail: [info@globestock.co.uk](mailto:info@globestock.co.uk)

<http://www.globestock.co.uk>

## G-TRIPOD OHP

A quality tripod which is durable and versatile, for confined space and down hole applications. Setup over the horizontal aperture the G-Tripod can be used in conjunction with the G-Saver II and or G-Winch. Used with the G-Saver II to protect personnel descending into or leaving a confined space, and with the G-Winch for lowering and raising personnel.

The Tripod has been designed to give a secure and stable anchorage for the G-Range of safety products. There are two anchorage points allowing the use of a secondary back-up fall arrestor, or other types of lifting / safety equipment. Accessories are available separately to facilitate this.



Manufactured in tubular aluminum for lightness and long term durability. The legs are telescopic and adjustable to accommodate uneven surfaces, and ensure easy transport and storage.

Rubber cup feet ensure stability in a wide variety of environments.

The G-Tripod can be supplied with brackets to suite the following equipment:

- 1) The G-Saver II or G-Stop
- 2) The G-Winch

Maximum Working Load: 136 kg.

Carries the  mark of approval.

Fully tested to European Standards.

Weight (Exc Brackets):	18 kg	
Height (Max):	2.4m	Length when closed: 1.70m
Leg Span (Max) Dia:	2.25m	
Max. Hole Dia:	1.75m	

Note: Globestock Ltd reserve the right to change specifications without prior notice