



Lanyards

Restraint Lanyards

GSE1030/1035

When working at height, restraint lanyards can prevent a user from falling by restricting access to an edge or preventing movement towards a hazardous area.

Restraint lanyards should not be used as part of a fall arrest system. For work restraint purposes only.

The maximum lifespan of webbing products is 10 years from purchase. The type of use and the conditions will affect the lifespan of a product.

Connectors are available separately (see below).

Restraint Lanyard (GSE1035)

Standard lengths are 1.5m and 2m, with other lengths available on request (minimum order quantities may apply).

Maximum recommended user weight: 150kg.

Colours may vary.

EN358

Adjustable Restraint Lanyard (GSE1030)

A restraint lanyard with an adjustable working length of 1.25 to 1.75 metres.

Adjustable to suit the working environment.

Maximum recommended user weight: 150kg.

Colours may vary.

EN358



Adjustable Restraint Lanyard GSE1030



070K



107K



1080-01



1080-03

Other connectors are available on request.



Globestock Limited, Mile Oak Industrial Estate
Maesbury Road, Oswestry, Shropshire, SY10 8GA. UK

T: +44 (0) 1691 654 966 F: +44 (0) 1691 661 726
info@globestock.co.uk www.globestock.co.uk @Globestock_Ltd

PL: 21, Issue: 07. Globestock Ltd reserve the right to change specifications without prior notice. © Globestock 2018.